


No time lost, more space gained

One day provides year-round usability from your heated garage

1

Your contractor will install the unit with the same quality you have come to trust




2

The Garage Guy is safe and simple to install — your contractor will take care of all the necessary connections



3

With the installation done, you can get back to the important things you need your garage for



Forget **3** season porch: time for the **4** season garage



Technical Data

Model	GG030	GG045	GG060	GG075	GG090
Garage Size*	1 Car	1-2 Car	2 Car	2-3 Car	3 Car
BTU Input	30,000	45,000	60,000	75,000	90,000
BTU Output	24,300	36,450	48,600	60,750	72,900
Thermal Efficiency	81%	81%	81%	81%	81%
Temperature Rise	60°	60°	60°	60°	60°
Voltage	115/1/60	115/1/60	115/1/60	115/1/60	115/1/60
Full Load Amps	3.0	3.0	3.7	4.1	6.4
Vent Diameter-Standard	4"	4"	4"	4"	4"
Vent Diameter-Sep. Combustion	4"	4"	4"	4"	5"
Weight (lbs.)	57	60	75	87	96
Dimensions	Height	13-1/4"	13-1/4"	16-13/16"	16-13/16"
	Width	30"	30"	30"	30"
	Depth	25-7/8"	25-7/8"	26-3/16"	26-3/16"
Clearance Required	Top	1"	1"	1"	1"
	Left (Control Box)	18"	18"	18"	18"
	Right	1"	1"	1"	1"
Back	18"	18"	18"	18"	18"
	Bottom	1"	1"	1"	1"

*Garage Guy installing contractor can recommend the correct unit for your garage.



Sterling HVAC Products is a division of Mestek, a leader in commercial and residential HVAC technologies

www.GarageGuyHeater.com

260 North Elm Street | Westfield, MA 01085 | 413-568-9571



Make the
Space
that's
all **yours** a space to go all year



you can keep going to the space that you keeps going

Even in **Winter**



The Dirt on Garage Guy Heaters

- space-saving design doesn't clutter work space
- quiet operation with impressive 81% efficiency
- ETL Certified for performance and safety
- direct spark ignition ensures safe, reliable start-up
- control temps easily with wall-mounted thermostat; compatible with programmable timer
- manufactured entirely in the USA